



The Xylanta SAINT3 family are the latest generation of products derived from the highly successful SAINT serial communications analysis tools originally developed by Delphi/Aptiv. These new products enhance the SAINT2 design by adding support for CAN-FD in addition to CAN 2.0B, whilst maintaining a high level of software and hardware compatibility with the older product.

The SAINT3 Pro is a flexible, cost-effective multi-protocol bus monitoring and logging tool designed with the needs of software developers and system testers in mind. USB based and highly portable, it suits a wide range of situations. The various interfaces can act as silent, packet monitors or have the ability to actively inject packets into the data streams. In addition, it is capable of performing standalone reflash and emulation.

It is supported by the included SAINT Bus Engine (SBE) and Bus Monitor. In addition an API is available allowing custom SBE plugins to be developed.

### Key Features

#### Flexible Multi-Bus Tool

- Supports multiple simultaneously active buses
- All interfaces support non-intrusive monitor only mode
- Consistent time-stamping across all interfaces
- Standalone reflash and emulation capable
- Extensible via plugin module option
- Drop in replacement for the SAINT2

#### CAN Bus Features

- Two independent ISO CAN-FD controllers
- Software selectable between various dual wire and single transceivers
- Detects and reports a wide range of message/bus errors

#### Other Interfaces


- KW2000, LIN, I2C data monitoring, Trigger I/O

#### Host Connection

- USB 2.0 High Speed Device and RS-232

#### Application Software

- Integrates with the SAINT Bus Engine (SBE)
- SBE provides an open API for software plugins
- Includes Bus Monitor plugin
- Software supports Windows 7, 10 and 11



### Applications

- Network diagnostics
- Logging
- Software download and firmware updates
- Gateway between buses
- Node simulation
- Automation of message testing
- And many others...

# Product Specification

## General Features

- Onboard 32-bit ARM processor with 16Mbytes external memory
- High Speed USB 2.0 interface (480Mbps)
- 16-bit timestamp giving 1milisecond resolution
- SD card for standalone operation (emulation, reflash)
- Supports add-in option board for functionality expansion
- Field upgradeable firmware design (flash firmware)
- SAINT2 compatible 25 way female D-Type connector for interface wiring
- Powered via D-Type for easy integration with external system

## CAN Bus Support

- Two independent ISO CAN-FD controllers with hardware filters
- Complies with CAN specifications 2.0 A/B and FD
- Selectable between FD (TJA1057), FT (TJA1055) and SW (MC33897) transceivers
- Support for ISO and non-ISO CAN-FD messaging
- Single wire interface supports high voltage wakeup, high speed mode and test tool resistor
- CAN bit rates from 25 kbit/s up to transceiver limit with non-standard speeds supported
- Detects and reports a wide range of message/bus errors
- CAN/CAN-FD termination resistors software controllable

## KW2000/LIN Bus Support

- Two independent KW2000/LIN channels
- Channel 1 supports KW2000 and LIN (L9637 transceiver, as per SAINT2)
- Channel 2 supports LIN only (TJA1021 transceiver)
- Full support for LIN 1.x/2.x and J2602
- Jumper selectable as master or slave
- Flexible baud rate selection

## I2C Bus Support

- I2C data monitoring (byte data)
- Internal (5V) or external bus voltage (0.9V-5.5V) jumper selectable

## Trigger Support

- 2 x trigger in and 2 x trigger out as per SAINT2

## Other

- Ships with USB cable and 25-way breakout board
- Requires external power (10-36V DC, 250mA typ @ 12V)
- Operating temperature -10C to +80C, 85% RH (non condensing)
- Compact, robust metal case (170mm x 108mm x 35mm)
- Weight 400g
- FCC and CE compliant
- One year limited warranty

# Host Software Support

## General Features

- Fully compatible with existing SAINT2 applications

## CAN SAINT Bus Engine (SBE)

- Allow detection of all SAINT compatible devices
- Provides an interface for selection and connection

## Bus Monitor Plugin

- Provides a scrolling message monitor
- Enhanced to support CAN-FD messages
- Supports message filtering, scripting, emulation and logging

## J2534

- Enhanced J2534 interface with CAN-FD support

## SDK



- Allows development of SBE plugins

## Other

- Requires Windows 7, 10 or 11

# Order Codes

- S3P-001 SAINT3 Pro with breakout board and 1m USB cable
- S3P-002 SAINT3 Pro without accessories



**Xylanta**  
Advanced Test Solutions

[www.xylanta.com](http://www.xylanta.com)

**For more information email: [sales@xylanta.com](mailto:sales@xylanta.com)**

The information contained herein is believed accurate at the time of writing and is subject to change without notice. Copyright © 2017-2024 Xylanta Ltd. All rights reserved. Xylanta and DeskLab are trademarks of Xylanta Ltd. Rev.8 October 2024.